

# VELA 3204 DS



External color fixation



\* 3.2m Four I3200 Print Heads Speed

<b>360 x 240dpi - 4 pass</b>	<b>100 m<sup>2</sup>/h</b>
<b>720 x 1800dpi - 6 pass</b>	<b>85 m<sup>2</sup>/h</b>

<b>Model</b>	VELA 3204 DS
<b>Head Print</b>	Four Epson I3200-U1 Print Heads
<b>Printing Technology</b>	Piezoelectric Inkjet
<b>Medidas aceptables</b>	Width 128 in (3250mm) Thickness Maximum 39 mil (1mm) Weight 176 lb.(80 kg)
<b>Printing Width</b>	126 in (3200mm)
<b>Ink Cartridges</b>	Type: Dye Sublimation Ink Capacity: 4*4 CISS (220ml ink cartridge with 1.5L ink tank) 6*6 CISS (6 color), 8*8 CISS (8 color) optional Color: 4 colors (Cyan, Magenta, Yellow, Black) 6 colors, 8 colors optional
<b>Printing Resolution</b>	Maximum 2400 dpi
<b>Printing Speed</b>	4 pass: 100 sqm/h 6 pass: 85 sqm/h
<b>Media Heating System</b>	Intergrated post printer heater & Fabric Heater
<b>Interface</b>	USB 3.0/LAN
<b>Power Supply</b>	AC 220V ± 10%, 50/60 HZ
<b>Dimensions (with stand)</b>	205 (W) x 43 (D) x 74 (H) in. (5200 (W) x 1100 (D) x 1890 (H) mm )
<b>Weight (with stand)</b>	2116 lb. (960 kg)
<b>Packaging Dimensions</b>	Printer: 194 (W) x 50 (D) x 69 (H) in. (4910 (W) x 1260 (D) x 1750 (H) mm ) Heater: Part 1: 175 (W) x 47 (D) x 55 (H) in. (4450 (W) x1200 (D) x 1400 (H) mm ) Part 2: 26 (W) x 22( D) x 4 (H) in. ( 650 (W) x 560 (D) x110 (H) mm )
<b>Packaging Weight</b>	Printer: 1080 lb. (490 kg) Heater: Part 1: 1058 lb. (480 kg); Part 2: 176 lb. (80 kg);
<b>Environment</b>	Power on: Temperature 59F to 90F (15°C to 32°C) 68F (20°C) // Humidity: 35 to 80% (no condensation). Power off: Temperature: 41F to 104F (5°C to 40°C) // Humidity: 20 to 80% (no condensation).
<b>Accessories</b>	USB cable, media clamp, manual, drain bottle, ink cartridges, RIP software, etc.






- Directly print on fabric.
- Print and heat without paper transfer.
- Vivid color performance with high color fastness.
- High performance chemical blower ensures friendly environment.



**EXTERNAL COLOR FIXATION**

<b>Model</b>	SR 3200
<b>First Power</b>	6000W
<b>Working Power</b>	2000W
<b>Working Width</b>	3200mm
<b>Working temperature</b>	160 - 240°C
<b>Working Speed</b>	20 - 100 M/H
<b>Power</b>	220 - 240 V, 16A 50/60HZ



High-precision and high-stability tensioning pulley system.



High quality DC servo motor with good stability and long life.



THK high-precision mute rail.



Stable Bulk System Ensures Amazing Printing Speed



Automatic moisturizing cleaning assembly ensures the stability of head cleaning and improves working stability.



New pinch roller structure of three in group brings more stable feeding precision.