



STRATUS

STRATUS FOAM EXTRAMAX 5/10mm

Description:

Foam product with expanded polystyrene laminated on both sides with a 250gr white paper ideal for direct printing. It is possible to print on both sides and stands out for its extra-white matt finish.

Ideal for interior decoration, shops and shops, department stores, museums.

POLYSTYRENE FOAM CORE CHARACTERISTICS	
Colour	Blanco
Melt Index	3
Mold Shrinkage	0.4 ~ 0.8
Tensile Strength	530
Elongation at Break	4
Flexural Strength	1,000
Izod Impact Strength	1
Rockwell Hardness	120
Heat Deflection Temperature	88°C
Vicat Softening Temperature	103°C
Flammability Test to UL 94	HB
Flammability Test to IEC 707	FH3-28

OVERLAY PAPER ON FOAM CORE CHARACTERISTICS	
Weight	250 ± 7
Thickness	252 ± 7
PH Value	6.5
Whiteness	126 ± 3%
Brightness	100 ± 3%

ADHESIVE GLUE & LINER CHARACTERISTICS	
Appearance	Acrylic Based Pressure Sensitive Adhesive
PH	4
Coating Thickness	40 ~ 50
Release Liner	90 gsm ± 3, PE Coated paper

Available in the online shop:

PL635510 - Stratus Foam Extramax 10mm 2060x3050mm

PL635500 - Stratus Foam Extramax 5mm 2060x3050mm

