

LONA BLOCKOUT MIDNIGHT FINE FR 510GR

Features:

- Double-sided printable
- Great smoothness
- Strong color expression
- Stable ink absorption
- Solvent, eco solvent, UV and latex printable

	UNIT	VALUE	TEST METHOD
Base Fabric	100%PES	-	DIN EN ISO2060
Construction	Weaving /inch	36x36	DIN60001
Weight of fabric	Gsm/m2	78 ± 5	DIN53352 BS3424
Weight of PVC	Gsm/m2	440 ± 5	DIN53352 BS3424
Total weight	Gsm/m2	510 ± 10	DIN53352 BS3424
Thickness	mm	0,40 ± 0,02	DIN EN ISO 2286-3
Width	cm	up to 320	-
Breaking strength	N/5cm	Warp: 1400	DIN53354 BS3424 Method6A
		Weft: 1080	
Tearing strength	N	Warp: 125	DIN53356 BS3424 Method7A
		Weft: 115	
Adhesion	N/5cm	80	DIN53357 BS3425 Method9B
Temperature resistance	°C	-20 to 70	DIN53357 BS3425
Lacquering	None		
Flammability	FR is B1 certificated		
Low cadmium & heavy metals	EN71-3 standard can be reached.		

The indexes above are on average, so there will be ±5% tolerance of actual indexes.

