

POSTERWALL SANDTEX PP HIGH TACK 120MIC

Description:

White polypropylene (PP) self-adhesive film with 120mic gritty texture and PVC free. High tack, water-based, resistant to the passage of time and with elastic permanent acrylate adhesive. Smooth matte surface. With FR B1 certificate.

The ecological alternative for difficult surfaces, PVC-free adhesive surface.

Advantage:

- Excellent color reproduction and print quality
- High dimensional stability
- High adhesive resistance

Compatible with latex and UV inks.

Available widths: 1,55m.

Applications:

Its high tack adhesive allows application on smooth and slightly rough walls, concrete, surfaces exposed to greater wear. Suitable for long-term indoor applications. Duration in outdoor applications (not printed) 2 years depending on the application and the surface.

It can be applied to 2D curved and planar surfaces.

FILM	MEASUREMENTS
Thickness	120mic
Gloss	<30
Dimensional stability	MD: ≤ + 0,1 CD: ≤ + 0,6
ADHESIVE	MEASUREMENTS
Value pH	7,0
Adhesive strength [N/25mm]	10 min: > 11 24h: > 14 AFERA 4001
Adhesive glass strength [N/25mm]	10 min: > 11 24h: > 13 AFERA 4001
MASKING	MEASUREMENTS
Thickness	155 ± 10 um
Weight	140 ± 5
Removing force [mN/cm]	40-100 speed 300 mm/min
OTHERS	MEASUREMENTS
Storage conditions	18° - 25°C HR: 40 - 65%
High energy surfaces	Adhesion on clean and dry surfaces > + 5 ° C / 41 ° F Film removal > + 5 ° C / 41 ° F
Less energy surfaces	Adhesion on clean and dry surfaces > + 5 ° C / 41 ° F Film removal > + 5 ° C / 41 ° F

Available in the shop online:

PL673320 - Posterwall PP Sandtex High Tack 1,55X50m

