



## LIQUID LAMINATOR SPLASH 1600WB



Liquid laminator designed to varnish solvent, eco-solvent and UV ink prints. Varnish coating protects ink prints on vinyl, canvas, canvas, wallpaper, truck tarps, etc.

### Features:

- ✓ Standard 0.5mm and 0.8mm mayer bar interchangeable.
- ✓ Fixed position for mayer bar
- ✓ Coating bar and thermal panel with vertical movement controlled by an air compressor
- ✓ Easy washing with water
- ✓ Empty varnish tank alarm system
- ✓ Varnish pumping and recycling system
- ✓ Interchangeable unwind and rewind shafts
- ✓ Variable speed control in both directions
- ✓ Automatic emergency safety shutdown button
- ✓ CE certified

	1600WB	2200WB
<b>Maximum coating width</b>	1600 mm	2200 mm
<b>Working speed</b>	0,5-1,5 m/min	0,5-1,5 m/min
<b>Maximum coating thickness</b>	32 microns	32 microns
<b>Recommended working temperature</b>	100-120 °C	100-120 °C
<b>Alarm temperature</b>	150 °C	150 °C
<b>Consumption</b>	AC 110V 230V 120W	AC 110V 230V 120W
<b>Power consumption</b>	6,5 Kw	7,5 Kw
<b>Power requirements</b>	380V/3P 50/60Hz 15A 220V/1P 50/60Hz 32A	380V/3P 50/60Hz 16A 220V/1P 50/60Hz 35A
<b>Machine dimensions</b>	2045x940x1055 mm	2490x965x1055 mm
<b>Packaging dimensions</b>	2150x1100x1230 mm	2490x1300x1230
<b>Weight</b>	390kg / 475kg	410kg / 540kg
<b>Optional mayer bar</b>	0,3mm / 1,0mm	0,3mm / 1,0mm

