

LONA FRONTLIT FUSION FR 510GR

Description:

High quality casted banner of 510gr, matt finishing.
It can be printed on solvent, eco solvent, UV and latex.
Weldable.

Applications:

Indoor and outdoor advertising; specially for advertising in sport halls, stadiums, exhibitions. For big format displays.

CHARACTERISTICS	VALUE	STANDARD
Material	100%PES	DIN EN ISO2060
Fabric density	1000 denier	DIN EN ISO2060
Construction	20x20 inch	DIN 60001
Total weight	510g/m ²	DIN53352 BS3424 method5A
Weight of fabric	170g/m ²	DIN53352 BS3424 method5B
Weight of PVC coating	340gr/m ²	DIN53352 BS3424 method5B
Tensile strength	warp: 2200N/5cm	DIN53354 BS3424 method6A
Tearing strength	weft: 1900N/5cm warp: 300N weft: 250N	DIN53356 BS3424 method7A
Adhesion	80N/5cm	DIN53357 BS3425 method9B
Temperature	-20°C +70°C	DIN53372 BS3424 method10
Flame retardancy	Yes	-
Lacquering	No	-

Available in the online shop:

PL677310 - Lona Frontlit Fusion Fr 510gr 5,00x50m
 PL676740 - Lona Frontlit Fusion Fr 510gr 5,00x50m
 PL676730 - Lona Frontlit Fusion Fr 510gr 3,20x50m
 PL676720 - Lona Frontlit Fusion Fr 510gr 2,50x50m
 PL676710 - Lona Frontlit Fusion Fr 510gr 1,60x50m
 PL676709 - Lona Frontlit Fusion Fr 510gr 1,60x25m
 PL676705 - Lona Frontlit Fusion Fr 510gr 1,37x50m
 PL676704 - Lona Frontlit Fusion Fr 510gr 1,37x25m
 PL676700 - Lona Frontlit Fusion Fr 510gr 1,06x50m
 PL676699 - Lona Frontlit Fusion Fr 510gr 1,06x25m

