

# TEXTIL RETINA BACKLIT 185GR SUBUV FR



## Description:

Ultra soft, elegant and dense fabric special for backlit aluminum profiles, very flexible and anti-wrinkle, ideal for sublimation and keder clothing.

## Applications:

Light box, frame systems.

CHARACTERISTICS	VALUES	STANDARD
<b>Material</b>	100% polyester	DIN600001, ASTM-D7641
<b>Weight</b>	185g/m2 5.4oz/sq.yd	DIN EN ISO 2286 - 2, ASTM - D751
<b>Weave Method</b>	Woven	-
<b>Yarn Dtex</b>	75x75x75 Denier	DIN EN ISO 2060, ASTM - D1907
<b>Transmission factor</b>	(49 + / -2) %	ANSI PH2.19 ISO5/2
<b>FR</b>	DIN 4102 -B1, NFPA 701 TEST 1	DIN 4102 - B1, NFPA 701 TEST 1
<b>Width</b>	Up to 3.2M/126"	DIN EN ISO 3759 ASTM - D751 - 2006
<b>Fixation Temperature</b>	190-210°C, 1-2min	-
<b>Yellowing Temperature</b>	≥210°C	-
<b>Ink</b>	Sublimation and UV	-

## Available in our online shop:

PL761160 - Textil Retina Backlit 185gr SUBUV FR 3,20x50m

