

LONA FRONTLIT FUSION BLACKBACK 510GR

Description:

High quality 510gr cast canvas with black back. Matte finish.

It can be printed in solvent, eco-solvent, UV and latex.

Weldable canvas.

Applications:

Ideal for indoor and outdoor advertising, advertising in stadiums or pavilions, exhibitions, building facades, large format displays, etc.

CHARACTERISTICS	VALOR	STANDARD
Material	1000Dx1000 Denier (High tenacity yarn) 100%PES	DIN EN ISO2060
Construction	20x20 Weaving /inch	DIN60001
Weight of fabric	175±5	DIN53352 BS3424 Method5B
Weight of PVC	335±5g/m2	DIN53352 BS3424 Method5B
Total weight	510±10g/m ²	DIN53352 BS3424 Method5A
Thickness	0.39±0.02mm	DIN EN ISO 2286-3
Widths	Hasta 510cm	-
Breaking resistance	Warp: 2200 N/5cm Weft: 1900 N/5cm	DIN53356 BS3424 método7A
Tearing resistance	Warp: 300 N Weft: 250 N	DIN53356 BS3424method7A
Adhesion	80 N/5cm	DIN53357 BS3425 Method9B
Temperature resistance	-20~70 °C	DIN53357 BS3425 Method10
Lacquering	No	-
Flammability	If the client need ,We can reach: B1, B2, NFPA701, DIN75200 etc	

