

TEXTIL RETINA BACKLIT 190GR SUBUV FR



Description:

Ultra soft, elegant and dense fabric special for backlit aluminum profiles, very flexible and anti-wrinkle, ideal for sublimation and keder clothing.

Applications:

Light box, frame systems.

CHARACTERISTICS	VALUE	STANDARD
Material	100% polyester	DIN600001, ASTM - D7641
Weight	190g/m2 5.6oz/sq.yd	DIN EN ISO 2286 - 2, ASTM -D751
Weave method	Woven	-
Yarn dtex	75x150	DIN EN ISO 2060, ASTM - D1907
Transmission factor	(51 + / -2)%	ANSI PH2.19 ISO5/2
FR	DIN 4102 - B1, NFPA 701 TEST1	DIN 4102 - B1, NFPA 701 TEST 1
Width	Up to 3.2M / 126"	DIN EN ISO 3759 ASTM - D751 - 2006
Fixation temperature	190-210°C, 1-2min	-
Yellowing temperature	≥210°C	-
Ink	Sublimation and UV	-

Available in our online shop:

PL761180 - TEXTIL RETINA BACKLIT DS 190GR SUBUV FR 2,60x50M

PL761190 - TEXTIL RETINA BACKLIT DS 190GR SUBUV FR 3,20X50M

