

WINDOWS PERFORATED VINYL 160MIC XPRESS

SPECIFICATION

- Soft, clear white monomeric 160mic self adhesive PVC film for smooth printing.
- Dynamic prints, perfect visibility due to 60:40 balance between vinyl and holes.
- Suitable for (eco) solvent and Latex.
- Indoor/Outdoor use.
- Easy to remove up till 6 months after application.

SPECIFICATION	DESCRIPTION	
PVC	Type	Calendered monomeric soft PVC film
	Thickness	160 ± 10 um
	Color Code	White
	Back	Black coating
	Shrinkage	≤ 0.8%
	Surface Tension	≥ 30dn/cm
	Opacity	> 99%
	Hole No.	Average 130/sq in
	Hole diameter	1,62mm
	Distance Between Holes	Left-right 1.25mm Up-down 2.0mm
ADHESIVE	Hole Space	40%
	Type	Clear solvent based removable pressure sensitive glue
	Weight (g/m2)	30±5
	Adhesion Temperature	15°C - 40°C
	180° Peeling Force	5N/25mm
	Initial Adhesion-Ball Tack	≥ 3N/25MM*25MM
	Holding Power	≥ 1440min
Removable Durability	One year cleanly removable glue on clean glass surface at temperature of 23-25°C and RH of 50-60% - it will not peel from the window or car if it is applied on flat surface within 2 year.	
LINER	Type	Laminated Kraft paper
	Color	White
	Weight	190±10g/m2
	Release Force	0,05-0,25N/25cm
Storage Period	12 months under ordinary condition at temperature of 22°C and relative humidity of 50-55%	
Application	One way vision - Outdoor digital and silk screen printing media for vehicle graphics, airport graphics, subway window, platform graphics, glass walls of building and signage display applications.	
Compatibility of machines and ink	Media is suitable for all solvent and eco solvent digital printers with heating system including Phaeton, Infiniti, Mimaki, Roland, Vutek and HP Scitex. Inks should be the original inks from the printer manufacturers. The best printing temperature is 35-40°C.	

Available in the online shop:

PL674840 - Vinilo Windows Perforado 160mic Xpress 1,52x50m

PL674820 - Vinilo Windows Perforado 160mic Xpress 1,37x50m

PL674800 - Vinilo Windows Perforado 160mic Xpress 1,06x50m

