

# PP SPIDER WHITE MATT FILM GREYBACK 120MIC

## Description:

Matt white PP high density printing film, 120mic.  
Removable adhesive with grey backing.  
Kraft paper backing with double PE liner 120gr.

## Characteristics:

- Compatible with eco-solvent, UV and latex inks. For the latter it is advisable to profile and colour test prior to any job to adjust colourimetric and densitometric values. Sticky ink should be avoided to prevent the coating from peeling off.
- High density PP for excellent tactile feel.
- Paper liner for easy application.

## Applications:

Widely used for indoor & short term outdoor advertising. Ideal for premium advertising applications.

## Available sizes:

1,07m, 1,37m and 1,52m.

CHARACTERISTICS	VALUE
Weight of finished product	227± 10
Thickness of finished product	260 ± 10
Weight of PP	85 ± 5
Thickness PP	105 ± 5
Thickness of Liner	127 ± 10
Weight Liner	120 ± 5
Indoor temperature	23 ± 2°C
Relative humidity	50 ± 5%
Applicable temperature	-20 ~+70
Shelf life	1 year: Should be stored in suitable conditions, preferably use within six months

## Storage condition:

All products always need to be stored in their original packing and with the original protection materials, preferably stored hermetically and vertically, do not expose to direct sunlight or heat sources. In order to avoid loss of quality, products should also be stored in suitable conditions, that is at a temperature of 25°C ± 5°C and a relative humidity of 50 ± 5%. Under these conditions, products can be stored up to one year.

## Production and Application Environment:

We recommend to using at a temperature of 23 ± 2°C, a relative humidity of 50%, clean dust-free environment without suspended matter, product shall be transferred to the printing environment in advance from the stored environment, the resting period depends on the storage environment; when printing, the ink temperature should be 18°C to 28°C, the best equipment preheating temperature is 30°C. As the solvent of ink is easy to cause the adhesive swelling during printing, we suggest to remain enough margins when printing, make the trimming, cold lamination and pasting after the image complete dry.

Application environment: at a temperature of 18°C to 28°C, a relative humidity of 50%, pasting on flat, smooth and clean surface without floating dust and shedding, it is necessary to take more than 2 hours for maintenance before laminating.

