

# POSTERWALL SANDTEX PP HIGH TACK 120MIC

## Description:

White polypropylene (PP) self-adhesive film with 120mic gritty texture and PVC free. High tack, water-based, resistant to the passage of time and with elastic permanent acrylate adhesive. Smooth matte surface. With FR B1 certificate.

The ecological alternative for difficult surfaces, PVC-free adhesive surface.

## Advantage:

- Excellent color reproduction and print quality.
- High dimensional stability.
- High adhesive resistance.

Compatible with latex and UV inks.

Available widths: 1,55m.

## Applications:

Its high tack adhesive allows application on smooth and slightly rough walls, concrete, surfaces exposed to greater wear. Suitable for long-term indoor applications. Duration in outdoor applications (not printed) 2 years depending on the application and the surface.

It can be applied to 2D curved and planar surfaces.

| FILM                  | MEASUREMENTS               |
|-----------------------|----------------------------|
| Thickness             | 120mic                     |
| Gloss                 | <30                        |
| Dimensional stability | MD: ≤ + 0,1<br>CD: ≤ + 0,6 |

  

| ADHESIVE                         | MEASUREMENTS                            |
|----------------------------------|---|
| Value pH                         | 7,0                                     |
| Adhesive strength [N/25mm]       | 10 min: > 11    24h: > 14    AFERA 4001 |
| Adhesive glass strength [N/25mm] | 10 min: > 11    24h: > 13    AFERA 4001 |

  

| MASKING                | MEASUREMENTS            |
|------------------------|-------------------------|
| Thickness              | 155 ± 10 um             |
| Weight                 | 140 ± 5                 |
| Removing force [mN/cm] | 40-100 speed 300 mm/min |

  

| OTHERS               | MEASUREMENTS   |
|----------------------|--|
| Storage conditions   | 18° - 25°C    HR: 40 - 65%   |
| High energy surfaces | Adhesion on clean and dry surfaces > + 5 ° C / 41 ° F<br>Film removal > + 5 ° C / 41 ° F |
| Less energy surfaces | Adhesion on clean and dry surfaces > + 5 ° C / 41 ° F<br>Film removal > + 5 ° C / 41 ° F |

## Available in the shop online:

PL673320 - Posterwall PP Sandtex High Tack 1,55X50m

