

# ADHESIVE BACK DOT REPOSICIONABLE

## Description:

On either side self-adhesive, cadmium free, transparent, monomeric soft vinyl film. One side all over coated with permanent, strong adhesive, the other side with dot-shaped adhesive for easy and bubble-free mounting.

Coated with a solvent free, age resistant and permanently elastic acrylate adhesive.

## Applications:

For challenging adhesions of heavy and difficult materials like textiles, synthetic leather, wallpaper, blackout flexface or banner materials on flat surfaces. Mounting film for photos, PE-paper, inkjet and digital prints on several surfaces such as hardfoam, smooth PVC surfaces, polystyrene, polycarbonate, Forex chipboard laminated, aluminium, etc.

Ideal for mounting on a wide range of graphic display boards and panels, trade fair constructions, window decorations and universal short term applications. Universally applicable for indoor use.

Transform any rigid or flexible support into repositionable:

- o Photographic or poster paper.
- o Polypropylene or polyester films.
- o PVC tarpaulin.
- o Rigid supports: feather board, pegasus, foamed pvc, polypropylene.

Save on assemblies, trips and displacement of the assemblers. Any backing adhesive bonded with Punto Dot Adhesive becomes easy to apply and repositionable.

Corrects application errors on the fly without leaving adhesive residue and keeping the original support intact.

## Advantages:

- o Easy to handle.
- o Strong adhesion.
- o The Dot system facilitates its application without bubbles.

FILM TECHNICAL CHARACTERISTICS			
Thickness	70 +/-4 mic		
Weight	90 +/-4 g/m2		
ADHESIVE SIDE 1 TECHNICAL CHARACTERISTICS			
Thickness	76 +/-5 mic		
Value pH	7,0 pH		
Adhesive strength [N/25mm]	10 min : >1,0	24h: >1,5	AFERA 4001
MASKING TECHNICAL CHARACTERISTICS			
Thickness	76 +/- 5 mic		
Weight	88 +/-3 mic		
Removal force [mN/cm]	60 +/-20 mN/cm		
ADHESIVE SIDE 2 TECHNICAL CHARACTERISTICS			
Value pH	7,0 pH		
Adhesive strength [N/25mm]	10 min : >1,0	24h: >1,5	AFERA 4001

