

## STRATUS PVC LITE

### Description:

Extruded and foamed low density PVC sheet with protective film on one side. Ideal substrate for direct printing and mounting of low cost applications.

Available thicknesses: 1, 3, 5, 10 and 19 mm.

### Applications:

- Trade fairs and shop decoration
- Displays
- In advertising
- Furniture construction
- Print support and flat mounting
- Space separation

### Technical data sheet:

	MEASURES
Density	0,460 g/cm <sup>2</sup>
Tensile modulus of elasticity	750 MPa
Modulus of elasticity in bending	850 MPa
Impact strength	10 kJ/m <sup>2</sup>
Bending strength	28 D (15s)
Average coefficient of linear thermal expansion	0.7 x 10 <sup>-4</sup> K
Surface strength	≥ 10 <sup>-4</sup> 1
Temperature range	De 0°C a 60°C

### Available in the online shop:

- PL640090 - STRATUS PVC Lite 1mm 3050X1530mm
- PL640095 - STRATUS PVC Lite 1mm 3050X2030mm
- PL640100 - STRATUS PVC Lite 3mm 3050X1530mm
- PL640110 - STRATUS PVC Lite 3mm 3050X2030mm
- PL640120 - STRATUS PVC Lite 5mm 3050X1530mm
- PL640130 - STRATUS PVC Lite 5mm 3050X2030mm
- PL640140 - STRATUS PVC Lite 10mm 3050X1530mm
- PL640150 - STRATUS PVC Lite 10mm 3050X2030mm
- PL640170 - STRATUS PVC Lite 19mm 3050X1530mm

