LAMINADO POLIÉSTER ANTIGRAFITI PG7036 UV

Description:

Polyester film (transparent gloss, 36mic) with an ultra clear solvent based acrylic adhesive (permanent), laminate on a one-sided silicone PE liner (50mic).

Particularly suitable for protection of digital prints and images to avoid influence of UV, dirt and humidity.

The perfect transparency of the film and the adhesive improve the chromatic quality and brightness of the image.

This product improves outdoor print duration and reduces fading and damage of the prints due to weather conditions.

Due to the good resistance of the polyester film to solvents, it can be successfully used as "anti-graffiti" film when proper felt pents are used.

Particularly suitable for the application on flat, curved and slightly corrugated surfaces.

Shelf life:

2 years when stored in the original packaging between 20°C and 25°C at 50% relative humidity.

Recomandations for laminating:

Please ensure the print is perfectly dry before laminating. We suggest to let the material dry for at leas! 48 hours after printing.

Standard dimensions:

1220 mm x 50 m 1370mm x 50m

CHARACTERISTICS	MEDIDA
Carrier	Clear Polyester Film
Thickness	36mic +/- 5 %
Adhesive	Ultra clear solvent acrylic, permanent
Adhesion	7,5 N/cm +/- 5%
Liner	one-sided silicone PE 50mic
Application temperature:	+10 - +40 °C
Temperature durability:	-40- +80 °C
Outdoor durability:	5-7 years

Available in the online shop:

PL665860 - CLEAR PET ANTI-GRAFFITTIV LAMINATE 36 MIC. 1,37 x 50m



Madrid · C/Mario Roso de Luna, 31-3 // Pol. Ind. Fin de Semana // 28022 Madrid (Madrid) //T: 910 382 775 SHOP ONLINE Barcelona · C/Els Plans de la Sala, 28 // Pol. Ind. Plans de la Sala // 08650 Sallent (Barcelona) // T: 938 372 565





posterand panel

